



HARDO Ortholine

- Speziell entwickelt für die Orthopädie-Schuhtechnik zum Anschluss an externe Filteranlagen
- Absaugwand extrem weit zurückgesetzt
- Automatische Bandspannung

HARDO Ortholine

- Specially designed for orthopaedic shoe technology and suitable for connection to external filter plants
- Suction wall extremely standing back
- Automatic belt tension



HARDO ORTHOLINE 115 B

Art. 04-61

- Orthopädie Fräs- und Schleifmaschine
- Zwillingsfräse (B-Fräse = Absatz- und Sohlenfräser)
- Absatzfrontkegel auf Bajonettverschluss
- Schleifbänder 1×40×Ø175 mm + 1×100×Ø100 mm
- Klappenbetätigung am jeweiligen Antrieb gekoppelt
- Einzelantrieb der Bänder
- Schleifarmatur auf Bajonettverschluss
- Bimser multiverstellbar
- Doppeldrucktaster
- Ergonomisches HARDO Design

- Farbe: hellgrau RAL 7035
- Elektr. Daten: 400V/3Ph/50Hz/3,2kW
- Maße: 1150×780×1855 mm (B×T×H)
- Gewicht: 325 kg

Änderungen vorbehalten 02/17

- Orthopaedic trimming- and sanding machine
- Twin trimmers (B-version = heel- and sole-trimmer)
- Heel breaster on bajonet
- Sanding belts 1×40×Ø175 mm + 1×100×Ø100 mm
- Flap activation connected to the respective driven
- Separate belt control
- Sanding wheel on bajonet
- Naumkeag multi-adjustable
- Button panel
- Ergonomic HARDO Design

- Colour: light grey RAL 7035
- Electr. specifications: 400V/3Ph/50Hz/3,2kW
- Dimensions: 1150×780×1855 mm (wxdxh)
- Weight: 325 kg

Modifications reserved 02/17